



# NEROLAC

## IMPRESSIONS ULTRA HD

RADIANT SHEEN LUXURY EMULSION

### PRODUCT DESCRIPTION

Ultra-High Definition Luxury Emulsion give your walls Radiant sheen with ultra HD colours and a smooth finish with excellent washability , superior stain-resistance and ultra-low odour .

### PERFORMANCE FEATURES & BENEFITS



### SURFACE PREPARATION

- 1** Ensure the surface is clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down, using suitable abrasive paper and thereafter wipe off
- 2** Apply a coat of suitable Nerolac Interior Primer Sealer followed by Nerolac Wall Putty to level the surface and make the surface uniform.
- 3** Apply again a coat of suitable Nerolac Interior Primer Sealer.
- 4** Then apply two to three coats of Nerolac Impressions Ultra HD.

### RECOMMENDED SYSTEM FOR APPLICATION

- 1** Thin 1-liter paint with maximum 300-400 ml of water. Apply 2-3 coats of ultra HD with an interval of 4-6 hours by brush or roller. Dark shade may require additional coat for hiding.



## TECHNICAL DATA



**COVERAGE\*\***  
150 - 170 Sq. ft/Ltr/Coat



**DRYING TIME**  
Surface Dry : 30 Minutes



**STABILITY OF THINNED PAINT**  
Use within 24 hours after thinning



**VOC**  
Ultra low VOC



**WASHABLE**  
High



**THINNING**  
30 - 40% by volume by water



**FLASH POINT**  
NA

**RECOATING**  
Min. 3 - 4 hrs. (@27°± 2°C & RH 60 ± 5%)



**GLOSS LEVEL**  
Sheen



**DRY FILM THICKNESS (IN MICRONS)/COAT**  
20 - 25 : Brush  
30 - 35: Roller



\*\*\* Actual covering capacity may vary depending upon the method & condition of application, surface condition temperature, wind velocity, application silk, surface roughness, surface porosity and shade

\*\*\* Paint with estimated VOC in the range of 5grams/liter without addition of colorant (Ref: KNP lab results). VOC content may vary from batch to batch.

## PRECAUTIONS



- 01) Refer MSDS for Ultra HD for safety measures & precautions.
- 02) Store in well-ambient conditions, ventilated locations & away from sources of ignition and fire.
- 03) Keep away from children.
- 04) In case of eye / skin contact, wash with plenty of water.
- 05) Inhalation / Injection can be dangerous. In either case, move to fresh air & consult medical practitioners.
- 06) Do not apply when ambient temperature might drop to levels below 10°C within 4 hrs of application.
- 07) New plaster should be allowed to cure for minimum 12 weeks.
- 08) Avoid extra thinning for better results.
- 09) Do not use Universal Stainers. Stir well paint before application.
- 10) The container must be tightly closed when not in use.

## POST APPLICATION INSTRUCTIONS

For removing stains, sponge clean with mild soap solution and wipe clean please allow 1 week of drying time to freshly painted wall for it to be ready for stain removal/cleaning

**PACK SIZES:**   
0.90 Ltr, 3.6 Ltr & 18 Ltr.

## COLOR:

As per Impressions Ultra HD Shade Card  
& Colour Scapes Fandeck.

## NO. OF SHADES POSSIBLE:

More than 1450.

## STORAGE

- Store in a cool dry place.
- Keep away from direct sunlight.
- Thinned paint to be consumed within 24 Hrs after thinning.

## SAFETY FEATURES



- Avoid inhalation, eye and skin contact in case of contact, wash with water and seek medical attention.
- Do not pour the leftovers in the drain dispose off after natural drying.
- Non-Flammable.