




## KANSAI NEROLAC SUROKHA EXTERIOR EMULSION

### PRODUCT DESCRIPTION

Nerolac Suraksha Exterior Emulsion is a water based exterior emulsion designed to impart good quality and luxurious appearance to exterior walls along with long lasting performance. It is suitable for dry or moderately humid climatic conditions.

### PERFORMANCE FEATURES & BENEFITS



### SURFACE PREPARATION

1. Ensure the surface is clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down, using suitable abrasive paper and thereafter wipe off.
2. Apply a coat of suitable Nerolac Exterior Primer Sealer followed by Nerolac All Purpose Putty to level the surface and make the surface uniform.
3. Then apply two to three coats of Nerolac Suraksha Exterior Emulsion.

### RECOMMENDED SYSTEM FOR APPLICATION

1. Primer\*\* (1 coat), Dry# in 4-6 h
2. All Purpose Putty##, Dry in 6-8 h
3. Finish Nerolac Surokha Exterior Emulsion (2-3 coats), Dry min. 4-6 h in between coats

### PRECAUTIONS

1. Refer MSDS of "Nerolac Surokha Exterior Emulsion" for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from the source of ignition and fire.
3. Keep away from children.
4. In case of eye/skin contact, wash with plenty of water.
5. Inhalation/Injection is dangerous. In either case, move to fresh air & consult medical practitioners.
6. Do not apply when ambient temperature might drop to level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results
9. Do not use universal strainers. Stir paint well before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipment's like rubber or polythene gloves, safety goggles/glasses & face mask.

## TECHNICAL DATA



\* Actual covering capacity may vary depending upon the method of application & condition of application, surface condition, temperature, wind velocity, application skills, surface roughness, surface porosity & shade.

## POST APPLICATION INSTRUCTIONS

For the best performance of paint, ensure proper washing and cleaning of all algae and fungal growth at regular intervals of 6 months.

	<b>SAFETY FEATURES</b> Non-Flammable		<b>PACK SIZE</b> 0.90 L, 3.6 L, & 18 L.
	<b>SHADE RANGE</b> As per Colour Scapes Fandek and shade card.		<b>NO. OF SHADES POSSIBLE</b> More than 1200
	<b>SHELF LIFE</b> 12 months from date of manufacture.		

## DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products, therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement, prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.